Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial Product Name FTC-ZS ZINC 400 ML

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses corrosion protection

1.3 Details of the supplier of the safety data sheet

Company designation fischerwerke GmbH & Co. KG

> Klaus-Fischer-Straße 1 D-72178 Waldachtal

Telephone: +49(0)7443 12-0 FAX: +49(0)7443 12-4222 Email: info-sdb@fischer.de Internet: www.fischer.de

Marketer AnchorMark Pty. Ltd.

Unit 1, 61 Waterview Close

Dandenong South VIC 3175, Australia Telephone: +61 (0) 3 97992096

FAX: +61 (0) 3 97992696

Email: info@anchormark.com.au

1.4 Emergency telephone number

Emergency telephone number +49(0)6132-84463 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regula- Aerosol 1; H222-229 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336

tion (EC) No. 1272/2008 STOT RE 2; H373 Aquatic Chronic 2; H411

2.2 Label elements

Hazard pictogram



GHS07



GHS08



GHS09

Signal word Danger

Hazardous component(s) to be in-

dicated on label

acetone, xylene, Hydrocarbons, C9, aromatics

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020 Print date: 19.11.2020 Version: 1/en

Replaces version from: 12.03.2020

H-statement(s) H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness. H319: Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated ex-

posure.

H411: Toxic to aquatic life with long lasting effects.

P101: If medical advice is needed, have product container or label at P-statement(s)

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do no expose to temperatures ex-

ceeding 50 °C/122 °F.

P501: Dispose of contents/container to special waste treatment.

Further information Pressurized container: protect from sunlight and do not expose to tem-

> peratures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Health hazard No information available.

Particular information pertaining

specific risk for human / environ-

ment

No information available.

No information available. Indication of danger No information available. Hazard precautions

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
zinc powder - zinc dust (stabilised)	CAS No.: 7440-66-6 EC-No.: 231-175-3 Index-No.: 030-001-01-9 REACH No.: 01-2119467174-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 20.0 %
propane	CAS No.: 74-98-6 EC-No.: 200-827-9 Index-No.: 601-003-00-5 REACH No.: 01-2119486944-21	Flam. Gas 1; H220 Press. Gas; H280	< 20.0 %

Commercial Product Name: FTC-ZS ZINC SPRAY

fischer 📖

Revision Date: 19.11.2020 Replaces version from: 12.03.2020 Version: 1/en Print date: 19.11.2020

Ingredient	CAS No.	Classification (EC) 1272/2008	Concentration
acetone	CAS No.: 67-64-1 EC-No.: 200-662-2 Index-No.: 606-001-00-8 REACH No.: 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	< 20.0 %
xylene	CAS No.: 1330-20-7 EC-No.: 215-535-7 Index-No.: 601-022-00-9 REACH No.: 01-2119488216-32, 02-2119752448-30	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	< 20.0 %
isobutane	CAS No.: 75-28-5 EC-No.: 200-857-2 Index-No.: 601-004-00-0 REACH No.: 01-2119485395-27	Flam. Gas 1; H220 Press. Gas; H280	< 20.0 %
Hydrocarbons, C9, aromatics	EC-No.: 918-668-5 REACH No.: 01-2119455851-35	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 STOT SE 3; H335 H336	< 10.0 %
ethylbenzene	CAS No.: 100-41-4 EC-No.: 202-849-4 Index-No.: 601-023-00-4 REACH No.: 02-2119752523-40	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearingorgans) Asp. Tox. 1; H304	< 2.5 %

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice Take off immediately all contaminated clothing.

In case of accident or unwellness, seek medical advice immediately (show

directions for use or safety data sheet if possible).

Wear personal protection equipment (refer to section 8).

If inhaled Provide fresh air.

In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

Do NOT use solvents or thinners.

In case of eye contact Remove contact lenses.

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmol-

ogist.

If accidentally swallowed rinse the mouth with plenty of water (only if the

person is conscious) and obtain immediate medical attention.

Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Special medical treatment Treat symptomatically.

Commercial Product Name: FTC-ZS ZINC SPRAY

B 11 B 1 40 44 0000

Revision Date: 19.11.2020 Version: 1/en



Print date: 19.11.2020

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media spray mist, (water), Water spray jet, alcohol resistant foam, carbon diox-

ide, Extinguishing powder

Extinguishing media which must not be used for safety reasons

Full water jet

5.2 Special hazards arising from the substance or mixture

Special exposure hazards arising Heating or fire can release toxic gas.

from the substance or prepara-

Pressurised container: May burst if heated.

tion itself, its combustion prod-

Fight fire with normal precautions from a reasonable distance.

ucts, or released gases5.3 Advice for firefighters

Special protective equipment for

firefighting

In case of fire: Wear self-contained breathing apparatus.

For the protection against direct skin contact, body protective clothing is

essential (in addition to the usual working clothes).

Additional information on fire-

fighting

Suppress (knock down) gases/vapours/mists with a water spray jet.

Keep containers and surroundings cool with water spray.

Do not allow water used to extinguish fire to enter drains, ground or wa-

terways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions For non-emergency personnel

Accidental release measures:

Wear personal protection equipment (refer to section 8).

Remove all sources of ignition.

Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Environmental precautions The product should not be allowed to enter drains, water courses or the

soil.

Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Allow stiffening. Take up mechanically.

Treat the recovered material as prescribed in the section on waste dis-

posal.

Commercial Product Name: FTC-ZS ZINC SPRAY

Commercial Froduct Name. FTC-23 ZiNC 3FK

Revision Date: 19.11.2020



Print date: 19.11.2020

6.4 Reference to other sections

Version: 1/en

Reference to other sections Reference to other sections: 7 / 8 / 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Vapours are heavier than air and may spread along floors. BEWARE:

Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

Do not spray on flames or red-hot objects.

Keep container tightly closed.

Hygiene measures: When using do not eat, drink or smoke. Wash hands

before breaks and after work.

Take off contaminated clothing and wash it before reuse.

Precautions Handle and open container with care.

Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire

No special measures are necessary.

and explosion

Take measures to prevent the build up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

Storage space and container re-

quirements

Container may rupture on heating. Keep/Store only in original container. Keep container tightly closed and dry.

Store in accordance with local regulations.

Unsuitable materials for contain-

ers

Keep only in original container.

Hints on storage assembly Keep away from food, drink and animal feedingstuffs.

German storage class 2B

Recommended storage tempera-

-1 u

ture

SECTION 8: Exposure controls/personal protection

+5 - 25 °C

8.1 Control parameters

acetone

Australia						
Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Source		
500	1185	1000	2375	WORKPLACE EX- POSURE STANDARDS FOR AIRBORNE CON- TAMINANTS 18.April 2013		

Commercial Product Name: FTC-ZS ZINC SPRAY



Revision Date: 19.11.2020

Version: 1/en Print date: 19.11.2020

Europe			
Long-term exposure value/	Long-term exposure value/	Issuing date	Source
mg/m3	ppm		
1 210	500	2000/39	DIRECTIVE 2009/161/EU

xylene

Australia					
Long-term exposure	Long-term exposure	Short-term exposure	Short-term exposure	Source	
value/ ppm	value/ mg/m3	value / ppm	value / mg/m3		
80	350	150	655	WORKPLACE EX-	
				POSURE STANDARDS	
				FOR AIRBORNE CON-	
				TAMINANTS 18.April	
				2013	

Europe						
Long-term ex- posure value/	0		Short-term ex- posure value /	Note	Issuing date	Source
ma/m2	n n no	mg/m3	nnm			
mg/m3	ppm	mg/ms	ppm			
221	50	442	100	Skin	2000/39	DIRECTIVE

ethylbenzene

Australia				
Long-term exposure value/ ppm	Long-term exposure value/ mg/m3	Short-term exposure value / ppm	Short-term exposure value / mg/m3	Source
100	434	125	543	WORKPLACE EX- POSURE STANDARDS FOR AIRBORNE CON- TAMINANTS 18.April 2013

Europe						
	0	Short-term ex- posure value / mg/m3	Short-term ex- posure value / ppm	Note	Issuing date	Source
442	100	884	200	Skin	2000/39	DIRECTIVE 2009/161/EU

8.2 Exposure controls

Respiratory protection In case of inadequate ventilation wear respiratory protection.

Hand protection Health injuries are not known or expected under normal use. For pro-

longed or repeated contact use protective gloves.

Suitable material Protective gloves complying with EN 374. Butyl caoutchouc (butyl rubber),

CR (polychloroprene, chloroprene rubber), NBR (Nitrile rubber), Fluorinat-

ed rubber

Unsuitable material PVC or rubber gloves are not recommended.

Material thickness adjust to application and duration of use

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020 Version: 1/en

Replaces version from: 12.03.2020

Print date: 19.11.2020

Break through time adjust to application and duration of use

Remarks Take note of the information given by the producer concerning perme-

ability and break through times, and of special workplace conditions (me-

chanical strain, duration of contact).

Replace when worn. Note

Eye protection Wear closely fitting protective glasses in case of splashes.

Safety glasses with side-shields conforming to EN166

Skin and body protection Long sleeved clothing

> Choose body protection according to the amount and concentration of Note

> > the dangerous substance at the work place.

General protective and hygiene

measures

Do not eat, drink or smoke when using this product.

Avoid contact with the skin and the eyes.

Wash hands and face before breaks and after work and take a shower if

necessary.

Keep away from food, drink and animal feedingstuffs. Use protective skin cream before handling the product.

Information on environmental

protection regulations

No special environmental measures are necessary.

see section 6/7

Provide adequate ventilation. Engineering measures

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form aerosol Colour grey

Odour acetone-like

Odour threshold not determined

No data available рΗ

Melting point [°C] / Freezing point

[°C]

No data available

No data available Boiling point [°C]

Initial boiling point [°C] and boil-

ing range [°C]

> 0

Flash point [°C] Not applicable. (aerosol)

No data available Evaporation rate [kg/(s*m²)] No data available Flammability (solid, gas)

Explosion limits [Vol-%]

Lower limit No data available

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020



Print date: 19.11.2020 Version: 1/en

No data available Upper limit

Vapour pressure [kPa] No data available

No data available Vapour density

0.92 Density [g/cm³]

> 20 °C Temperature

Relative density No data available

No data available Solubility

No data available Water solubility [g/l]

Solubility [g/l] No data available

Partition coefficient n-octanol /wa-

ter (log P O/W)

No data available

Autoinflammability not auto-flammable

Decomposition temperature [°C] No data available

No data available Viscosity, dynamic [kg/(m*s)]

Viscosity, kinematic [mm²/s] No data available

not explosive. In use, may form flammable/explosive vapour-air mixture. Explosive properties

Risk of explosion. In use, may form flammable/explosive vapour-air mixture.

No Oxidising properties

9.2 Other information

Ignition temperature [°C] > 200

Miscibility with water immiscible

Solvent content [%] 67.7

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions. Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Chemical stability Stable when applying the recommended regulations for storage and han-

dling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Hazardous reactions No hazardous reaction when handled and stored according to provisions.

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



10.4 Conditions to avoid

Conditions to avoid The mixture is chemically stable under recommended conditions of stor-

age, use and temperature.

Direct sources of heat. Risk of bursting.

10.5 Incompatible materials

Materials to avoid Strong acids and oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition prod- No known hazardous decomposition products.

ucts

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Oral toxicity [mg/kg]

Hazardous ingredients

propane	
Value	Source
No data available	Company data

acetone			
Value	Test criterion	Test species	Source
> 5800	LD50	rat	Company data

xylene			
Value	Test criterion	Test species	Source
3523	LD50	rat	Company data

isobutane	
Value	Source
No data available	Company data

Hydrocarbons, C9, aromatics				
Value Test criterion Test species Source				
> 2000	LD50	rat	Company data	

ethylbenzene			
Value	Test criterion	Test species	Source
3500	LD50	rat	Company data

Dermal toxicity [mg/kg]

Hazardous ingredients

propane	
Value	Source
No data available	Company data

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



Replaces version from: 12.03.2020 Print date: 19.11.2020

acetone			
Value	Test criterion	Test species	Source
> 20000	LD50	rabbit	Company data

xylene			
Value	Test criterion	Test species	Source
2000	LD50	Rabbit	Company data

isobutane	
Value	Source
No data available	Company data

Hydrocarbons, C9, aromatics				
Value Test criterion Test species Source				
> 2000	LD50	rat	Company data	

ethylbenzene			
Value	Test criterion	Test species	Source
17800	LD50	rat	Company data

Inhalative toxicity [mg/l] Hazardous ingredients

propane				
Value	Test criterion	Test species	Exposure dura-	Source
			tion	
20	LC50	rat	4 h	Company data

acetone				
Value	Test criterion	Test species	Exposure dura- tion	Source
76	LC50	rat	4 h	Company data

xylene				
Value	Test criterion	Test species	Exposure dura- tion	Source
21,7	LC50	rat	4 h	Company data

isobutane				
Value	Test criterion	Test species	Exposure dura- tion	Source
> 50	LC50	rat	4 h	Company data

Hydrocarbons, C9, aromatics					
Value	Test criterion	Test species	Exposure dura- tion	Source	
> 6193	LC50	rat	4 h	Company data	

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



Replaces version from: 12.03.2020 Print date: 19.11.2020

ethylbenzene			
Value	Test criterion	Test species	Source
1432	LC50	rat	Company data

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish [mg/l]

Hazardous ingredients

propane			
Value	Test criterion	Exposure duration	Source
> 1000	LC50	96 h	Company data

acetone				
Value	Test criterion	Test species	Exposure dura- tion	Source
6210	LC50	Pimephales promelas (fat- head minnow)	96 h	Company data

xylene				
Value	Test criterion	Test species	Exposure dura- tion	Source
2,6	LC50	Salmo gairdneri	96 h	Company data

isobutane	
Value	Source
27,98	Company data

ethylbenzene			
Value	Test criterion	Exposure duration	Source
5,1	LC50	96 h	Company data

Toxicity to daphnia [mg/l]

Hazardous ingredients

propane				
Value	Test criterion	Test species	Exposure dura-	Source
		-	tion	
14,22	LC50	Daphnia magna (Big water flea)	48 h	Company data

acetone				
Value	Test criterion	Test species	Exposure dura- tion	Source
8800	EC50	Daphnia magna (Big water flea)	48 h	Company data

Safety Data Sheet as per regulation (EC) 1907/2006 Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



Replaces version from: 12.03.2020 Print date: 19.11.2020

xylene				
Value	Test criterion	Test species	Exposure dura- tion	Source
165	EC50	Daphnia magna (Big water flea)	48 h	Company data

isobutane		
Value	Source	
14,22	Company data	

Hydrocarbons, C9, aromatics					
Value	Test criterion	Test species	Source		
1 - 10	LC50	Daphnia magna (Wa- ter flea)	Company data		

ethylbenzene				
Value	Test criterion	Test species	Exposure dura- tion	Source
> 1,8	LC50	Daphnia magna (Big water flea)	48 h	Company data

Toxicity to algae [mg/l]

Hazardous ingredients

propane				
Value	Test criterion	Test species	Exposure dura- tion	Source
7,71	EC50	Scenedesmus quadricauda (Green algae)	96 h	Company data

xylene				
Value	Test criterion	Test species	Exposure dura- tion	Source
2,2	EC50	Selenastrum capricornutum	73 h	Company data

isobutane	
Value	Source
7,71	Company data

ethylbenzene				
Value	Test criterion	Test species	Exposure dura- tion	Source
7,7	EC50	Skeletonema costatum	96 h	Company data

NOEC (daphnia) [mg/l] Hazardous ingredients

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



Replaces version from: 12.03.2020 Print date: 19.11.2020

ethylbenzene	,			
Value	Test criterion	Test species	Exposure dura- tion	Source
1	NOEC	Daphnia magna (Big water flea)	7 d	Company data

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Disposal considerations Do not allow to enter into surface water or drains.

Dispose of waste according to applicable legislation.

Empty remaining contents.

Empty packaging: Where possible recycling is preferred to disposal or in-

cineration.

Product: Can be disposed of as a solid waste or burned in a suitable in-

stallation subject to local regulations.

Waste Code The following Waste Codes are only suggestions:

160504 - gases in pressure containers (including halons) containing dan-

gerous substances

150104 - metallic packaging

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG	Air transport ICAO/IATA
14.1 UN-No	1950	1950	1950
14.2 Description of the	AEROSOLS	AEROSOLS	AEROSOLS
goods			
14.3 Transport hazard	2	2.1	2.1
class(es)			
14.5 Environmental hazards	Dangerous for the environ-	Dangerous for the environ-	Dangerous for the environ-
	ment	ment	ment
Remarks	inflammable	(maximum 1 L) flammable	
Labels	2.1,U (1)	2.1,U	2.1,U (1)
Category	2		
Classification Code	5F		
Tunnel restriction code	D		
UN proper shipping name		AEROSOLS	Aerosols, flammable
Danger releasing substance		Naphtha (petroleum), hy-	
		drotreated light	
EmS		F-D;S-U	
Stowage category		A	
	•		,

14.6 Special precautions for user

Precautions No special measures are necessary.

Commercial Product Name: FTC-ZS ZINC SPRAY

Davida - Datas 40 44 2020

Revision Date: 19.11.2020



Replaces version from: 12.03.2020 Print date: 19.11.2020

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to

not applicable

Annex II of MARPOL and the IBC

Code

Version: 1/en

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC 66,5 % / 616,0 g/l

Decopaint regulation not relevant

Carcinogenic hazardous sub-

No

stance as per Annex II GefStoffV

Restriction of occupation. no restriction

Classification in compliance with the Industrial Safety Regulation Extremely flammable

15.2 Chemical safety assessment

Safety assessment For this preparation a chemical safety assessment has been carried out.

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2,

8, 9, 12, 15 and 16 of this safety data sheet.

Additional regulations This Safety Data Sheet is prepared according to Commission Regulation

(EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evalua-

tion, Authorisation and Restriction of Chemicals (REACH)

SECTION 16: Other information

Modifications since last version Modifications of the previous version are denoted with an asterisk (*).

Relevant H-phrases H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated ex-

posure.

Commercial Product Name: FTC-ZS ZINC SPRAY

Revision Date: 19.11.2020

Version: 1/en



Print date: 19.11.2020

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects. H411: Toxic to aquatic life with long lasting effects.

Wording of the hazard classes Aquatic Acute: Hazardous to the aquatic environment

Aquatic Chronic: Hazardous to the aquatic environment

Flam. Gas: Flammable gas Flam. Liq.: Flammable liquid Eye Irrit.: Serious eye irritation

STOT SE: Specific target organ toxicity - single exposure

Acute Tox.: Acute toxicity Skin Irrit.: Skin irritation Asp. Tox.: Aspiration hazard

STOT RE: Specific target organ toxicity - repeated exposure

Aerosol: aerosols

Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification	Evaluation
Aerosol 1; H222 H229	Experimental data
Skin Irrit. 2; H315	Calculated
Eye Irrit. 2; H319	Calculated
STOT SE 3; H336	Calculated
STOT RE 2; H373	Calculated
Aquatic Chronic 2; H411	Calculated

Modifications of the previous version are denoted with an asterisk (*).

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.